



Portable Autoclave LPOA-A16

www.labtron.com | info@Labtron.com

Overview

Portable autoclave LPOA-A16 is a 24 L electric heated top loading high pressure steam sterilizing unit with a sterilizing temperature of 126 °C. It is a Class N autoclave with complete leak proof chamber and a timer range of 0 ~ 60 min providing efficient sterilization process resulting in destruction of all living organisms. The lid of the instrument is a hand wheel, making it easy to use rather than the conventional knobs.

Features :

Working temperature : 126 °C

Overheating and pressure warning indicator

Digital display for working status with touch type screen

Indicator light to indicate the working

Automatic beep indication at the end of every cycle

Low water level indicator automation

Stainless steel sterilizing baskets

Reliable and safe self-inflating leak proof chamber

Dual scale indicating pressure gauge

Inner and outer chamber constructed by Stainless steel

Electric heated

Specifications :

Volume of Chamber	24 L
Working temperature	126 °C
Heating mode	Electrically heated
Timer range	0 ~ 60 min
Working pressure	0.14 ~ 0.16 MPa
Max safety pressure	0.165 MPa
Heat average	$\leq \pm 1^{\circ}\text{C}$
Temp adjustment	105 ~ 126 °C
Power	AC 220 V / 50 Hz
Overall Dimension	410 × 410 × 630 mm
Net Weight	18 Kg
Gross Weight	20 Kg

Applications :

Used in industries to sterilize equipment, bacteriological and research laboratories, medical, clinical and pharmaceutical industries



Quatro House, Lyon Way, Camberley, Surrey GU16 7ER United Kingdom

Email: info@Labtron.com | Website: www.labtron.com